



Siemens

CRI

Piezo

1. 30230

4H2Q-9K546-AE

TESTING

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
RL	1600	600	----	1000	49,6°	----	35,0 ±20,0
		FM		----	T , °C	, 3	, 3
		1	☒		63,7°	----	<b>69,2</b>
	P,	t,	U,	n, 1/	T , °C	, 3	, 3
RL	250	540	----	1000	51,2°	----	5,0 ±3,0
		FM		----	T , °C	, 3	, 3
		1	☑		46,3°	----	<u>7,03</u>
	P,	t,	U,	n, 1/	T , °C	, 3	, 3
VE	800	200	----	1000	50,0°	4,3 ±0,6	----
		FM		----	T , °C	, 3	, 3
		1	☒		52,2°	<b>5,07</b>	<u>6,22</u>
	P,	t,	U,	n, 1/	T , °C	, 3	, 3
LL	300	475	----	1000	49,0°	8,3 ±1,3	----
		FM		----	T , °C	, 3	, 3
		1	☒		45,2°	<b>6,80</b>	<u>7,75</u>
	P,	t,	U,	n, 1/	T , °C	, 3	, 3
EM	1000	600	----	1000	48,7°	29,2 ±2,0	----
		FM		----	T , °C	, 3	, 3
		1	☒		52,6°	<b>17,8</b>	<u>19,6</u>
	P,	t,	U,	n, 1/	T , °C	, 3	, 3
VL	1600	900	----	1000	52,8°	50,8 ±4,0	----
		FM		----	T , °C	, 3	, 3
		1	☒		64,7°	<b>44,7</b>	19,7