



" " , .29

Siemens

CRI

Piezo

1.

5WS40536

CODING IIC

1

9DDHJE

	P,	t,	U,	n, 1/	T , °C	, <sup>3</sup>	, <sup>3</sup>
RL	1350	----	----	1000	24,6°	----	35,0 ±25,0
				----	T , °C	, <sup>3</sup>	, <sup>3</sup>
		1	✓		24,1°	----	11,2
	P,	t,	U,	n, 1/	T , °C	, <sup>3</sup>	, <sup>3</sup>
RL	250	----	----	1000	24,6°	----	5,0 ±3,0
				----	T , °C	, <sup>3</sup>	, <sup>3</sup>
		1	✓		24,1°	----	3,30
	P,	t,	U,	n, 1/	T , °C	, <sup>3</sup>	, <sup>3</sup>
VE	800	----	----	1000	24,6°	2,0 ±0,5	----
				IIC	T , °C	, <sup>3</sup>	, <sup>3</sup>
		1	✓	✓	24,1°	1,92	----
	P,	t,	U,	n, 1/	T , °C	, <sup>3</sup>	, <sup>3</sup>
LL	250	----	----	1000	24,5°	6,8 ±1,3	----
				IIC	T , °C	, <sup>3</sup>	, <sup>3</sup>
		1	✓	✓	24,1°	7,40	----
	P,	t,	U,	n, 1/	T , °C	, <sup>3</sup>	, <sup>3</sup>
EM	1200	----	----	1000	24,6°	28,3 ±2,2	----
				IIC	T , °C	, <sup>3</sup>	, <sup>3</sup>
		1	✓	✓	24,1°	29,1	----
	P,	t,	U,	n, 1/	T , °C	, <sup>3</sup>	, <sup>3</sup>
VL	1600	----	----	1000	24,6°	52,4 ±4,0	----
				IIC	T , °C	, <sup>3</sup>	, <sup>3</sup>
		1	✓	✓	24,1°	50,9	----