



Siemens

CRI

Piezo

1. 30230

4H2Q-9K546-AE

TESTING

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
RL	1600	600	----	1000	46,6°	----	35,0 ±20,0
		FM		----	T , °C	, 3	, 3
		1	☑		61,3°	----	36,6

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
RL	250	540	----	1000	48,5°	----	5,0 ±3,0
		FM		----	T , °C	, 3	, 3
		1	✗		44,2°	----	8,22

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
VE	800	200	----	1000	47,5°	4,3 ±0,6	----
		FM		----	T , °C	, 3	, 3
		1	☑		50,5°	3,90	11,5

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
LL	300	475	----	1000	47,1°	8,3 ±1,3	----
		FM		----	T , °C	, 3	, 3
		1	✗		44,1°	6,87	7,69

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
EM	1000	600	----	1000	47,2°	29,2 ±2,0	----
		FM		----	T , °C	, 3	, 3
		1	☑		51,8°	29,8	15,1

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
VL	1600	900	----	1000	50,3°	50,8 ±4,0	----
		FM		----	T , °C	, 3	, 3
		1	✗		63,1°	55,3	41,6