



Siemens

CRI

Piezo

1. 30230

4H2Q-9K546-AE

TESTING

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
RL	1600	600	----	1000	44,3°	----	35,0 ±20,0
		FM		----	T , °C	, 3	, 3
		1	☑		52,5°	----	<u>20,7</u>

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
RL	250	540	----	1000	44,7°	----	5,0 ±3,0
		FM		----	T , °C	, 3	, 3
		1	☑		41,8°	----	<u>7,36</u>

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
VE	800	200	----	1000	44,5°	4,3 ±0,6	----
		FM		----	T , °C	, 3	, 3
		1	☑		47,1°	<u>4,50</u>	<u>6,76</u>

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
LL	300	475	----	1000	44,1°	8,3 ±1,3	----
		FM		----	T , °C	, 3	, 3
		1	☑		42,7°	<u>7,07</u>	<u>7,53</u>

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
EM	1000	600	----	1000	44,6°	29,2 ±2,0	----
		FM		----	T , °C	, 3	, 3
		1	☒		49,0°	<u>34,5</u>	<u>18,2</u>

	P,	t,	U,	n, 1/	T , °C	, 3	, 3
VL	1600	900	----	1000	48,6°	50,8 ±4,0	----
		FM		----	T , °C	, 3	, 3
		1	☒		61,5°	<u>43,3</u>	17,4